

SINCE 1805

Dreadnought
TILES

TILELINE RIDGE ROLL

BENEFITS

- All aluminium construction, AA fire rated and has design life in excess of 30 years. Conforms to Dry Fix Standard BS 8612.
- Provides high level ventilation at 5,000mm²/m, quick and easy to install in 6m lengths - no ridge unions
- Universal - fits most ridges and hips. Stainless steel clips provide mechanical fix and even ridge tile spacing. Optional H clips available for use with crested ornamental ridges
- Screw sleeve prevents light bleed between ridges (if required). Hooded ventilation design prevents water ingress.

Specification clause:

Mechanically-fixed ventilated ridge and hip system to be TILELINE RidgeRoll supplied by Dreadnought Tiles, Pensnett, Brierley Hill West Midlands Tel: 01384 78361 Fax: 01384 74553 E: sales@dreadnoughttiles.co.uk
Dry fix system to provide high level roof ventilation and ensure mechanical fixing of ridge and hip tiles to BS 8612. To be continually installed to provide ventilation area equivalent to 5000mm²/m to comply with Building Regulations Approved Document C2 and BS 5250. System to be fixed in accordance with [Dreadnought Tiles instructions](#).

Dreadnought Tiles, Hinton Perry & Davenhill Ltd, Dreadnought Works, Pensnett, Brierley Hill, West Midlands DY5 4TH
Tel: 01384 77405 Fax 01384 74553 Email: sales@dreadnought-tiles.co.uk Website: www.dreadnought-tiles.co.uk

