



## TILELINE ABUTMENT VENT

### BENEFITS

- Guaranteed 5000mm<sup>2</sup>/m ventilation provision to comply with BS 5250 and Building Regulations.
- Deluge and driving rain resistant as well as preventing large insect ingress.
- Unobtrusive when installed. Hidden within the roof flashings.
- Each unit overlaps the next to ensure integrity of flashing.
- Quick and easy to install. Does not affect the normal laying of the roof covering.
- Can be used in conjunction with traditional "lead roll details"

This system provides unobtrusive ventilation to top edge abutments of lean-to roofs and ensures a continuous ventilation gap of 5,000mm<sup>2</sup>/m. It is recommended to be used together with the Tileline eaves ventilation system to ensure through ventilation of the roof space from low to high level. It is supplied in a pack of 6 x 1m lengths and can be used in conjunction with traditional "lead roll" details.

There a number of applications for the abutment vent, including in front of dormer windows, below roof lights and below glazing features.

Specification clause:  
 Install Tileline Abutment vent supplied by Dreadnought Tiles, Pensnett, Brierley Hill West Midlands Tel: 01384 78361 Fax: 01384 74553 E: [sales@dreadnought-tiles.co.uk](mailto:sales@dreadnought-tiles.co.uk) under suitable flashing to provide ventilation to the roof-space equivalent to 5000mm<sup>2</sup>/m in accordance with Building Regulations and BS 5250.  
 Install continuously as shown on [Dreadnought Tiles instructions](#)



Dreadnought Tiles, Hinton Perry & Davenhill Ltd, Dreadnought Works, Pensnett, Brierley Hill, West Midlands DY5 4TH  
 Tel: 01384 77405 Fax 01384 74553 Email: [sales@dreadnought-tiles.co.uk](mailto:sales@dreadnought-tiles.co.uk) Website: [www.dreadnought-tiles.com](http://www.dreadnought-tiles.com)

