

## Statement of Verification

BREG EN EPD No.: 000002

Issue 4

ECO EPD Ref. No. 000092

This is to verify that the

### Environmental Product Declaration

provided by:

### The Brick Development Association

is in accordance with the requirements of:

**EN 15804:2012+A1:2013**

and

**BRE Global Scheme Document SD207**

This declaration is for:

**BDA Generic Brick**



### Company Address

The Building Centre  
26 Store Street  
London  
WC1E 7BT



  
Signed for BRE Global Ltd

Laura Crition  
Operator

19 February 2019  
Date of this Issue

27 February 2019  
Date of First Issue

18 February 2024  
Expiry Date



This Statement of Verification is issued subject to terms and conditions (for details visit [www.greenbooklive.com/terms](http://www.greenbooklive.com/terms)).

To check the validity of this statement of verification please, visit [www.greenbooklive.com/check](http://www.greenbooklive.com/check) or contact us.

BRE Global Ltd., Garston, Watford WD25 9XX.  
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: [Enquiries@breglobal.com](mailto:Enquiries@breglobal.com)



# Environmental Product Declaration

**EPD Number: 000002**

## General Information

| EPD Programme Operator  | Applicable Product Category Rules   |
|---|---|
| BRE Global<br>Watford, Herts<br>WD25 9XX<br>United Kingdom  | BRE Environmental Profiles 2013 Product Category Rules for Type III environmental product declaration of construction products to EN 15804:2012+A1:2013 |
| Commissioner of LCA study   | LCA consultant/Tool   |
| Brick Development Association (BDA) Ltd<br>26 Store Street<br>Fitzrovia<br>London<br>WC1E 7BT<br>United Kingdom   | Fei Zhang<br>BRE<br>Bucknalls Lane<br>Watford<br>WD25 9XX   |
| Declared/Functional Unit  | Applicability/Coverage  |
| 1 tonne of brick  | Sector UK Average   |
| EPD Type  | Background database   |
| Cradle to Gate with all options plus module D   | ecoinvent   |
| Demonstration of Verification   |   |
| CEN standard EN 15804 serves as the core PCR <sup>a</sup>   |   |
| Independent verification of the declaration and data according to EN ISO 14025:2010<br><input type="checkbox"/> Internal <input type="checkbox"/> External  |   |
| (Where appropriate <sup>b</sup> ) Third party verifier:<br><a href="#">Click here to enter text.</a>  |   |
| a: Product category rules<br>b: Optional for business-to-business communication; mandatory for business-to-consumer communication (see EN ISO 14025:2010, 9.4)  |   |
| Comparability   |   |
| Environmental product declarations from different programmes may not be comparable if not compliant with EN 15804:2012+A1:2013. Comparability is further dependent on the specific product category rules, system boundaries and allocations, and background data sources. See Clause 5.3 of EN 15804:2012+A1:2013 for further guidance |   |

## Information modules covered

| Product                             |                                     |                                     | Construction                        |                                     | Use stage                           |                                     |                                     |                                     |                                     |                                     |                                     | End-of-life                         |                                     |                                     |                                     | Benefits and loads beyond the system boundary |
|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|---|
|                                     |                                     |                                     |                                     |                                     | Related to the building fabric      |                                     |                                     |                                     | Related to the building             |                                     |                                     |                                     |                                     |                                     |                                     |   |
| A1                                  | A2                                  | A3                                  | A4                                  | A5                                  | B1                                  | B2                                  | B3                                  | B4                                  | B5                                  | B6                                  | B7                                  | C1                                  | C2                                  | C3                                  | C4                                  | D   |
| Raw materials supply                | Transport                           | Manufacturing                       | Transport to site                   | Construction – Installation         | Use                                 | Maintenance                         | Repair                              | Replacement                         | Refurbishment                       | Operational energy use              | Operational water use               | Deconstruction demolition           | Transport                           | Waste processing                    | Disposal                            | Reuse, Recovery and/or Recycling potential    |
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/>           |

Note: Ticks indicate the Information Modules declared.

## Manufacturing sites

Manufacturing data was provided by members of the BDA covering 46 UK manufacturing sites and representing 99% of UK brick production. Manufacturers and site addresses are included in the LCA report.

## Construction Product:

### Product Description

Bricks have a wide range of applications across the construction industry. Most bricks are used in cavity walls in building projects. Bricks generally form the outside face of the wall. Protected by the outer brick there is an insulation filled cavity (either full-filled or part-filled), an internal skin of thermal blockwork, a timber or steel framed structure, finished with either dry lined or a wet plastered finish which completes a typical wall. Bricks are also used fair faced internally replacing the internal blockwork and plasterwork, and for both free standing walls and civil engineering structures.

The members of the BDA manufacture a wide variety of bricks, which can vary in composition, colour, texture, size and production process. There are four main manufacturing processes by which bricks are produced in the UK; extrusion, soft mud moulding, handmade moulding and semi-dry pressing. In the UK, 'extrusion' and 'soft mud' are dominant. This LCA is for a generic UK brick which covers all brick types and production process and is based on data representative of 99% brick production by BDA member companies (with complete data returns from eight companies across 46 manufacturing sites).

### Technical Information

Bricks are made to a range of specifications, so characteristics can vary. The basic characteristics of the BDA average UK brick can be seen in the table below. The weight of a standard brick was given as supplied by the BDA to allow conversion of the results per declared unit to a per average brick basis. As other characteristics such as fire resistance and compressive strength vary between types of brick, this information can be found on the datasheets of specific bricks.

| Property         | Value, Unit               |
|------------------|---------------------------|
| Dimensions       | 215 mm x 102.5 mm x 65 mm |
| Dry brick weight | 2.13 kg                   |

All UK manufactured bricks are produced according to the requirements of BS EN 771-1: Specification for masonry units: Clay masonry units

## Main Product Contents

According to BDA, the average UK brick contains no substances that are listed in the ‘Candidate List of Substances of very high concern for authorisation’. The composition of the average product modelled in this project is obtained from the total raw material usages supplied by all participating members.

Composition of the BDA average brick based on input masses of used raw materials can be seen in the table below.

| Material/Chemical Input | %  |
|-------------------------|----|
| Clays and shales        | 92 |
| Sand                    | 6  |
| Inorganic additive      | 2  |

## Manufacturing Process

Most brickworks have their own onsite quarry or are in close proximity to one. However, depending on the type of clay required, clay can also be sourced from quarries further afield. Once extracted from the quarry, the raw clay undergoes a series of processes, which generally includes crushing and mixing with water, in order to transform it into a malleable material.


As mentioned previously there are four main manufacturing processes by which bricks are produced in the UK, although extrusion and soft mud moulding are the most dominant. The majority of UK clay types can be used, although the harder less clay rich shales and marls lend themselves more to extrusion with the more clay rich clays used in the soft mud process.

The extrusion process typically produces bricks with perforations within the body of the brick, ranging from highly perforated units through to the more traditional 3 and 10 holes. The perforations aid in the formation process of the bricks allowing the clay to be compressed in the extrusion die, however the main benefits come from the drying and firing process, where the additional voids within the bricks, not only reduce the amount of raw material in the brick, but also increases the surface area thus allowing for more efficient drying and firing.

The extrusion process is also often described as wire cut, as the column of clay is pushed out of the extrusion head the bricks are formed by a wire cutter normally cutting a number of bricks in the column. These bricks are then dried prior to entering the kiln for vitrifying which normally takes place at around 1000°C. Soft mud bricks are typically ‘solid’ or ‘frogged’ in appearance. The ‘frog’ is the name given to the indentation typically on the upper bedface of the brick, and again reduces the amount of raw material in the brick, and increases the surface area, thus again aiding drying and firing. The frog also aids the structural performance when laid with mortar. Soft mud bricks or ‘stock’ bricks have higher water absorbency prior to being dried. The characteristic sanded face is part of the requirement to allow the green brick to be released from the mould. After firing and cooling, bricks are sorted, packaged, and then stored in the stockyard or distributed.

## Process flow diagram

Typical process flow for the manufacture of moulded clay bricks, provided by the BDA can be seen below.



### Construction Installation

Bricks are generally hand by laid, on-site, with a cementitious or lime based mortar to bond the individual units together.

## Use Information

The service life of the BDA average UK brick is given as minimum of 150 years for a half brick thick cavity wall. For a full brick construction the minimum life expectancy is 600 years. These figures are derived from a 2007 research thesis by the Engineering and Physical Sciences Research Council. No maintenance of brickwork is expected for a minimum of 60 years. The most common maintenance required at this stage is the repointing of mortar.

## End of Life

At the end of life there are a number of common scenarios for brickwork. Firstly brickwork can be dismantled, with the individual units being separated, clean and reused. Secondly the brickwork can be demolished, broken down to a smaller aggregate size and used for a variety of purposes, such as foundation construction.

## Life Cycle Assessment Calculation Rules

### Declared / Functional unit description

The declared unit is 1 tonne of BDA average UK brick over a 60 year study period.

### System boundary

In accordance with the modular approach as defined in EN 15804:2012, this cradle-to-gate with all options plus module D EPD, includes the processes covered in the manufacturing, construction, use and end-of-life stages, as well as considering a benefits and loads beyond the system boundary scenario. The modules covered are A1-A3, A4, A5, B1 – B7, C1 – C4 and D.

### Data sources, quality and allocation

Specific primary data derived from total site data provided by BDA members, covering 46 manufacturing sites in the UK, has been modelled. In accordance with the requirements of EN 15804, the most current available data at the time of collection, has been used, covering the period of 1<sup>st</sup> January 2017 to 31<sup>st</sup> December 2017. Secondary data has been used for upstream and downstream processes that are beyond the control of the manufacturer such as raw material production. SimaPro v8 software was used to carry out the LCA modelling with background LCI datasets taken from the ecoinvent v3.2 database.

As total values used to create the stated production output were supplied, no allocation was required. For transport of fuels and of packaging materials to site, a nominal value of 50 km by road was assumed.

### Cut-off criteria

Full data collected by the BDA as supplied by BDA members for 46 UK manufacturing sites was used. The inventory process in this LCA includes all data related to raw material, packaging material, and their associated transport to the manufacturing site. Process energy and water use, direct production waste, non-production waste, wastewater to sewer, and emissions to air generated by the firing of the green bricks, are included.

## LCA Results

The results for the declared unit of 1 tonne of BDA average UK brick can be found below. As the average brick is assumed by the BDA to have a mass of 2.13 kg, results can be calculated per average brick by dividing individual values in results tables by a factor of (1000 / 2.13).

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

|   |                                      |      | Parameters describing environmental impacts |                            |                                    |   |  |                         |  |
|---|--------------------------------------|------|---|----------------------------|------------------------------------|---|--|-------------------------|--|
|   |                                      |      | GWP<br>kg CO <sub>2</sub><br>equiv.         | ODP<br>kg CFC 11<br>equiv. | AP<br>kg SO <sub>2</sub><br>equiv. | EP<br>kg (PO <sub>4</sub> ) <sup>3-</sup><br>equiv. | POCP<br>kg C <sub>2</sub> H <sub>4</sub><br>equiv. | ADPE<br>kg Sb<br>equiv. | ADPF<br>MJ, net<br>calorific<br>value. |
| Product stage   | Raw material supply                  | A1   | AGG   | AGG                        | AGG                                | AGG   | AGG  | AGG                     | AGG                                    |
|   | Transport                            | A2   | AGG   | AGG                        | AGG                                | AGG   | AGG  | AGG                     | AGG                                    |
|   | Manufacturing                        | A3   | AGG   | AGG                        | AGG                                | AGG   | AGG  | AGG                     | AGG                                    |
|   | Total (of product stage)             | A1-3 | 213   | 1.85e-5                    | 3.49                               | 0.107   | 0.177  | 1.24e-4                 | 2370                                   |
| Construction process stage                                | Transport                            | A4   | 16.7  | 3.08e-6                    | 0.0559                             | 0.0148  | 0.00975  | 4.40e-5                 | 253                                    |
|   | Construction                         | A5   | 63.7  | 3.64e-6                    | 0.313                              | 0.0479  | 0.0249   | 4.47e-5                 | 429                                    |
| Use stage   | Use                                  | B1   | MNR   | MNR                        | MNR                                | MNR   | MNR  | MNR                     | MNR                                    |
|   | Maintenance                          | B2   | MNR   | MNR                        | MNR                                | MNR   | MNR  | MNR                     | MNR                                    |
|   | Repair                               | B3   | MNR   | MNR                        | MNR                                | MNR   | MNR  | MNR                     | MNR                                    |
|   | Replacement                          | B4   | MNR   | MNR                        | MNR                                | MNR   | MNR  | MNR                     | MNR                                    |
|   | Refurbishment                        | B5   | MNR   | MNR                        | MNR                                | MNR   | MNR  | MNR                     | MNR                                    |
|   | Operational energy use               | B6   | MNR   | MNR                        | MNR                                | MNR   | MNR  | MNR                     | MNR                                    |
|   | Operational water use                | B7   | MNR   | MNR                        | MNR                                | MNR   | MNR  | MNR                     | MNR                                    |
| End of life   | Deconstruction, demolition           | C1   | MNR   | MNR                        | MNR                                | MNR   | MNR  | MNR                     | MNR                                    |
|   | Transport                            | C2   | 0.251                                       | 4.62e-8                    | 8.39e-4                            | 2.21e-4   | 1.46e-4  | 6.61e-7                 | 3.79                                   |
|   | Waste processing                     | C3   | 3.20  | 5.88e-7                    | 0.0245                             | 0.00610   | 0.00421  | 1.10e-6                 | 46.2                                   |
|   | Disposal                             | C4   | 1.03  | 2.73e-7                    | 0.00724                            | 0.00239   | 0.00120  | 1.47e-6                 | 25.4                                   |
| Potential benefits and loads beyond the system boundaries | Reuse, recovery, recycling potential | D    | -16.0                                       | -1.83e-6                   | -0.0978                            | -0.0283   | -0.0121  | -7.70e-5                | -229                                   |

GWP = Global Warming Potential;  
 ODP = Ozone Depletion Potential;  
 AP = Acidification Potential for Soil and Water;  
 EP = Eutrophication Potential;

POCP = Formation potential of tropospheric Ozone;  
 ADPE = Abiotic Depletion Potential – Elements;  
 ADPF = Abiotic Depletion Potential – Fossil Fuels;

## LCA Results (continued)

| Parameters describing resource use, primary energy        |                                      |      | PERE   | PERM     | PERT   | PENRE | PENRM | PENRT |
|---|--------------------------------------|------|--------|----------|--------|-------|-------|-------|
|   |                                      |      | MJ     | MJ       | MJ     | MJ    | MJ    | MJ    |
| Product stage   | Raw material supply                  | A1   | AGG    | AGG      | AGG    | AGG   | AGG   | AGG   |
|   | Transport                            | A2   | AGG    | AGG      | AGG    | AGG   | AGG   | AGG   |
|   | Manufacturing                        | A3   | AGG    | AGG      | AGG    | AGG   | AGG   | AGG   |
|   | Total (of product stage)             | A1-3 | 120    | 1.85e-4  | 120    | 2430  | 0     | 2430  |
| Construction process stage                                | Transport                            | A4   | 3.35   | 1.25e-5  | 3.35   | 251   | 0     | 251   |
|   | Construction                         | A5   | 71.6   | 6.22e-5  | 71.6   | 542   | 0     | 542   |
| Use stage   | Use                                  | B1   | MNR    | MNR      | MNR    | MNR   | MNR   | MNR   |
|   | Maintenance                          | B2   | MNR    | MNR      | MNR    | MNR   | MNR   | MNR   |
|   | Repair                               | B3   | MNR    | MNR      | MNR    | MNR   | MNR   | MNR   |
|   | Replacement                          | B4   | MNR    | MNR      | MNR    | MNR   | MNR   | MNR   |
|   | Refurbishment                        | B5   | MNR    | MNR      | MNR    | MNR   | MNR   | MNR   |
|   | Operational energy use               | B6   | MNR    | MNR      | MNR    | MNR   | MNR   | MNR   |
|   | Operational water use                | B7   | MNR    | MNR      | MNR    | MNR   | MNR   | MNR   |
| End of life   | Deconstruction, demolition           | C1   | MNR    | MNR      | MNR    | MNR   | MNR   | MNR   |
|   | Transport                            | C2   | 0.0503 | 1.87e-7  | 0.0503 | 3.76  | 0     | 3.76  |
|   | Waste processing                     | C3   | 0.274  | 6.37e-7  | 0.274  | 45.5  | 0     | 45.5  |
|   | Disposal                             | C4   | 0.776  | 2.12e-6  | 0.776  | 25.6  | 0     | 25.6  |
| Potential benefits and loads beyond the system boundaries | Reuse, recovery, recycling potential | D    | -12.6  | -3.68e-5 | -12.6  | -241  | 0     | -241  |

PERE = Use of renewable primary energy excluding renewable primary energy used as raw materials;  
 PERM = Use of renewable primary energy resources used as raw materials;  
 PERT = Total use of renewable primary energy resources;

PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials;  
 PENRM = Use of non-renewable primary energy resources used as raw materials;  
 PENRT = Total use of non-renewable primary energy resource



## LCA Results (continued)

| Parameters describing resource use, secondary materials and fuels, use of water |                                      |      |     |                           |                           |                |
|---|--------------------------------------|------|-----|---------------------------|---------------------------|----------------|
|   |                                      |      | SM  | RSF                       | NRSF                      | FW             |
|   |                                      |      | kg  | MJ<br>net calorific value | MJ<br>net calorific value | m <sup>3</sup> |
| Product stage   | Raw material supply                  | A1   | AGG | AGG                       | AGG                       | AGG            |
|   | Transport                            | A2   | AGG | AGG                       | AGG                       | AGG            |
|   | Manufacturing                        | A3   | AGG | AGG                       | AGG                       | AGG            |
|   | Total (of product stage)             | A1-3 | 0   | 0                         | 0                         | 0.861          |
| Construction process stage  | Transport                            | A4   | 0   | 0                         | 0                         | 0.0547         |
|   | Construction                         | A5   | 0   | 0                         | 0                         | 0.571          |
| Use stage   | Use                                  | B1   | MNR | MNR                       | MNR                       | MNR            |
|   | Maintenance                          | B2   | MNR | MNR                       | MNR                       | MNR            |
|   | Repair                               | B3   | MNR | MNR                       | MNR                       | MNR            |
|   | Replacement                          | B4   | MNR | MNR                       | MNR                       | MNR            |
|   | Refurbishment                        | B5   | MNR | MNR                       | MNR                       | MNR            |
|   | Operational energy use               | B6   | MNR | MNR                       | MNR                       | MNR            |
|   | Operational water use                | B7   | MNR | MNR                       | MNR                       | MNR            |
| End of life   | Deconstruction, demolition           | C1   | MNR | MNR                       | MNR                       | MNR            |
|   | Transport                            | C2   | 0   | 0                         | 0                         | 8.21e-4        |
|   | Waste processing                     | C3   | 0   | 0                         | 0                         | 0.00797        |
|   | Disposal                             | C4   | 0   | 0                         | 0                         | 0.0286         |
| Potential benefits and loads beyond the system boundaries                       | Reuse, recovery, recycling potential | D    | 0   | 0                         | 0                         | -0.373         |

SM = Use of secondary material;  
RSF = Use of renewable secondary fuels;

NRSF = Use of non-renewable secondary fuels;  
FW = Net use of fresh water

## LCA Results (continued)

| Other environmental information describing waste categories |                                      |      | HWD     | NHWD   | RWD      |
|---|--------------------------------------|------|---------|--------|----------|
|   |                                      |      | kg      | kg     | kg       |
| Product stage   | Raw material supply                  | A1   | AGG     | AGG    | AGG      |
|   | Transport                            | A2   | AGG     | AGG    | AGG      |
|   | Manufacturing                        | A3   | AGG     | AGG    | AGG      |
|   | Total (of product stage)             | A1-3 | 1.39    | 5.41   | 0.00697  |
| Construction process stage                                  | Transport                            | A4   | 0.106   | 11.8   | 0.00174  |
|   | Construction                         | A5   | 25.5    | 5.45   | 0.00295  |
| Use stage   | Use                                  | B1   | MNR     | MNR    | MNR      |
|   | Maintenance                          | B2   | MNR     | MNR    | MNR      |
|   | Repair                               | B3   | MNR     | MNR    | MNR      |
|   | Replacement                          | B4   | MNR     | MNR    | MNR      |
|   | Refurbishment                        | B5   | MNR     | MNR    | MNR      |
|   | Operational energy use               | B6   | MNR     | MNR    | MNR      |
|   | Operational water use                | B7   | MNR     | MNR    | MNR      |
| End of life   | Deconstruction, demolition           | C1   | MNR     | MNR    | MNR      |
|   | Transport                            | C2   | 0.00159 | 0.177  | 2.61e-5  |
|   | Waste processing                     | C3   | 0.0292  | 0.0235 | 3.32e-4  |
|   | Disposal                             | C4   | 0.0191  | 100    | 1.57e-4  |
| Potential benefits and loads beyond the system boundaries   | Reuse, recovery, recycling potential | D    | -0.218  | -5.36  | -0.00114 |

HWD = Hazardous waste disposed;  
 NHWD = Non-hazardous waste disposed;  
 RWD = Radioactive waste disposed

## LCA Results (continued)

| Other environmental information describing output flows – at end of life |                                      |      |      |     |     |                       |
|--|--------------------------------------|------|------|-----|-----|-----------------------|
|  |                                      |      | CRU  | MFR | MER | EE                    |
|  |                                      |      | kg   | kg  | kg  | MJ per energy carrier |
| Product stage  | Raw material supply                  | A1   | AGG  | AGG | AGG | AGG                   |
|  | Transport                            | A2   | AGG  | AGG | AGG | AGG                   |
|  | Manufacturing                        | A3   | AGG  | AGG | AGG | AGG                   |
|  | Total (of product stage)             | A1-3 | 33.6 | 0   | 0   | 0                     |
| Construction process stage   | Transport                            | A4   | 0    | 0   | 0   | 0                     |
|  | Construction                         | A5   | 51.7 | 0   | 0   | 0                     |
| Use stage  | Use                                  | B1   | MNR  | MNR | MNR | MNR                   |
|  | Maintenance                          | B2   | MNR  | MNR | MNR | MNR                   |
|  | Repair                               | B3   | MNR  | MNR | MNR | MNR                   |
|  | Replacement                          | B4   | MNR  | MNR | MNR | MNR                   |
|  | Refurbishment                        | B5   | MNR  | MNR | MNR | MNR                   |
|  | Operational energy use               | B6   | MNR  | MNR | MNR | MNR                   |
|  | Operational water use                | B7   | MNR  | MNR | MNR | MNR                   |
| End of life  | Deconstruction, demolition           | C1   | MNR  | MNR | MNR | MNR                   |
|  | Transport                            | C2   | 0    | 0   | 0   | 0                     |
|  | Waste processing                     | C3   | 0    | 0   | 0   | 0                     |
|  | Disposal                             | C4   | 900  | 0   | 0   | 0                     |
| Potential benefits and loads beyond the system boundaries                | Reuse, recovery, recycling potential | D    | 0    | 0   | 0   | 0                     |

CRU = Components for reuse;  
MFR = Materials for recycling

MER = Materials for energy recovery;  
EE = Exported Energy

## Scenarios and additional technical information

The beyond-the-gate scenarios modelled and relevant quantities, are described in the table below. Note that unless otherwise stated, values are per declared unit (i.e. per tonne) of BDA average UK brick.

| Scenarios and additional technical information |  |                          |         |
|--|--|--------------------------|---------|
| Scenario                                       | Parameter  | Units                    | Results |
| A4 – Transport to the building site            | As brick delivery could be to almost anywhere, an distance of 100 km was assumed to allow simple extrapolation of results to further distances, if necessary. Fuel consumption and capacity utilisation are as specified in the ecoinvent v3.2 dataset used (Transport, freight, lorry 16-32 metric ton, EURO5 {GLO}  market for   Alloc Def, U)   |                          |         |
|  | Lorry - diesel   | Fuel consumption (g/tkm) | 2.5     |
|  | Distance   | km                       | 100     |
|  | Capacity utilisation (incl. empty returns)   | %                        | 24      |
|  | Bulk density of transported products   | kg/m <sup>3</sup>        | 1485    |
| A5 – Installation in the building              | It is assumed that for whatever purpose the brick will have within a building or construction, mortar will be required to install the brick. The mortar quantity required as well as its composition, has been based on that used in the GreenGuide for brick and mortar external walls (element 806470537). Wastage percentages are also based that element. Uplifts of the equivalent percentage have been applied to A1-A3 and A4, and added to module A5, accordingly. It is assumed that the mortar will come from a supplier local to the installation site and a value of 25 km has been assumed for the supply distance. |                          |         |
|  | Ancillary material: mortar (cement to sand 1:4, w/c 0.5)   | kg                       | 252     |
|  | Transport of mortar to construction site   | km                       | 25      |
|  | Installation wastage to reuse: brick<br>Installation wastage to landfill: mortar (cement to sand 1:4, w/c 0.5)   | %<br>%                   | 5<br>10 |
| B1 – Use                                       | Bricks do not emit any emissions to air during their use, so this module is not relevant (MNR).  |                          |         |
| B2 – Maintenance                               | Bricks once installed require no maintenance themselves, so this module is not relevant (MNR).   |                          |         |
| B3 – Repair                                    | It is assumed that the brick should not need any repair during its service life or the study period, so this module is not relevant (MNR).   |                          |         |
| B4 – Replacement                               | The service life of the brick is at least as long as the 60-year study period and likely life of the building so no replacements are expected. Therefore, this module is not relevant (MNR).   |                          |         |
| B5 – Refurbishment                             | It has been assumed that no refurbishment action that relates to the brick will be required during the 60-year study period, so this module is not relevant (MNR)  |                          |         |
| Reference service life                         | The BDA gives a service life of 150 years for the brick  |                          |         |
| B6 – Use of energy                             | No energy is required for the brick to 'operate' during its use. Therefore, this module is not relevant (MNR).   |                          |         |
| B7 – Use of water                              | No water is required for the brick to 'operate' during its use. Therefore, this module is not relevant (MNR).  |                          |         |
| C1 – End-of-life deconstruction                | It is assumed that as when the brick is removed from its structure, this is part of demolition of the whole structure. Therefore, impacts must be allocated to the whole structure and it is assumed that those allocated to the brick alone are negligible, and can be assumed to be zero.  |                          |         |

| Scenarios and additional technical information |   |                          |         |
|--|---|--------------------------|---------|
| Scenario                                       | Parameter   | Units                    | Results |
| C2 – End-of-life transport                     | As will be described in module C3 and C4, 10% of the declared unit is assumed to go to landfill whilst the remaining 90% exits the system boundary to be reused on site. It is assumed that the landfill site is local and 15 km away from the construction site. As per module A4, fuel consumption and capacity utilisation are as specified in the ecoinvent v3.2 dataset used (Transport, freight, lorry 16-32 metric ton, EURO5 {GLO}  market for   Alloc Def, U)  |                          |         |
|  | Lorry - diesel  | Fuel consumption (g/tkm) | 2.5     |
|  | Distance  | km                       | 15      |
|  | Capacity utilisation (incl. empty returns)  | %                        | 24      |
|  | Bulk density of transported products  | kg/m <sup>3</sup>        | 1485    |
| C3 End-of-life pre-processing                  | As described in module C4 (below), it is assumed that 100% of the brick rubble is crushed. The diesel consumption value was provided and derived by the BDA based on data from members' crushing operations.  |                          |         |
|  | Diesel consumption for crushing   | litres                   | 0.88    |
| C4 End-of-life disposal                        | This scenario is based on a 90% reuse / 10% landfill split of construction waste, as evidenced in the UK Government statistics on waste (see references). The scenario supplied by the BDA and modelled in this project, assumes that once the wall containing the brick has been knocked down, 100% of it is crushed onsite. Only 90% of the resulting crushed brick is then usable to go on and leave the system boundary as recycled aggregate onsite, and the remaining 10% is not suitable for reuse, meaning that it goes to landfill   |                          |         |
|  | Crushed brick leaving system as recycled aggregate:   | kg                       | 900     |
|  | Crushed brick going to landfill:  | kg                       | 100     |
| Module D                                       | After demolition clay brick is crushed on site and used as a replacement of virgin aggregate in onsite roadwork or used as a replacement for normal weight coarse aggregate in the manufacture of concrete blockwork. 1 ton of crushed clay brick results in a (net) production of 900 kg of recycled secondary aggregate with 100 kg to landfill from crushing. This recycled secondary aggregate can in turn replace 900 kg of virgin aggregate. The ecoinvent v3.2 dataset used to represent avoided impacts of virgin aggregate was: Gravel, crushed {GLO}  market for   Alloc Def, U |                          |         |

## Interpretation

Figure 1 shows that for the production stage (modules A1 to A3), the majority of the total GWP value arises from onsite energy usage, which includes the use of natural gas, electricity, coal and coke, diesel and LPG fuels. The second highest contributor is from the emissions released from the clay raw materials on firing. The other input processes have relatively low contributions to the total GWP value by comparison.




Figure 1: GWP per tonne values by contributing input process

## References

BSI. Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products. BS EN 15804:2012+A1:2013. London, BSI, 2013.

BSI. Environmental labels and declarations – Type III Environmental declarations – Principles and procedures. BS EN ISO 14025:2010 (exactly identical to ISO 14025:2006). London, BSI, 2010.

BSI. Environmental management – Life cycle assessment – Principles and framework. BS EN ISO 14040:2006. London, BSI, 2006.

BSI. Environmental management – Life cycle assessment – requirements and guidelines. BS EN ISO 14044:2006. London, BSI, 2006.

Brick Development Association. The UK Clay Brickmaking Process, p.4. London, UK, 2017.  
<https://brick.org.uk/admin/resources/g-the-uk-clay-brickmaking-process.pdf>

Department for Environment Food & Rural Affairs. Government Statistical Service, UK Statistics on Waste, 2018:  
[https://assets.publishing.service.gov.uk/government/uploads/system/uploads/attachment\\_data/file/68305/1/UK\\_Statisticson\\_Waste\\_statistical\\_notice\\_Feb\\_2018\\_FINAL.pdf](https://assets.publishing.service.gov.uk/government/uploads/system/uploads/attachment_data/file/68305/1/UK_Statisticson_Waste_statistical_notice_Feb_2018_FINAL.pdf) Accessed 14<sup>th</sup> December 2018.