

1 Unique identification of product type

Ketley Staffordshire Quarry Tile
Group HD, Category II, 215x102.5x18mm, Clay Masonry Units

2 Type batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4):

KQT

3 Intended use or uses of the construction product in accordance with the applicable harmonised technical specification as foreseen by the manufacturer:

Clay Quarry Tiles for internal and external uses for rigid forms of construction

4 Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 (5):

Ketley Brick Company Ltd, Dreadnought Works, Dreadnought Road, Brierley Hill,

5 System or systems of assessment and verifications of constancy of performance of the construction product as set out in Annex V

System 4

6 Declared performance:

Essential Characteristics	Essential Characteristics	Harmonised Technical Specification
Dimensions and Dimensional Tolerances	Meets requirements for extruded tiles Group A1b	BS EN 14411:2016
Water Absorption	≤3.0%	BS EN 14411:2016
Frost Resistance	Complies after 100 cycles	BS EN 14411:2016
Breaking Strength	≥1100 N	BS EN 14411:2016
Slip/Skid Resistance (Pendulum)	Rz Value 20+µm PTV Value 36+ (Low Slip Potential)	BS 7976-2:2002
Stain Resistance	Minimum Class 3	BS EN 14411:2016
Deep Abrasion Resistance (Unglazed)	≤275mm ³	BS EN 14411:2016
Slip Resistance (Wet barefoot ramp)	Category C	DIN 51097:1992
Slip Resistance (Shod Ramp)	R11	DIN 51130:2010

7 The performance of the identified in points 1&2 conforms with the declared performance in point 6

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer

R. Dyer

Name: Richard Dyer

Position: Managing Director

Date: 1st January 2026